



柔光片



防眩网

*可选配件



产品特性

- 灯具颜色: 金属灰+白色面板
- 主体材质: 压铸铝
- 光学系统: 透镜+面板
- 灯具外观: 金属质感
- 投射方向: 垂直0~30°、水平0~355°
- 防护等级: IP20 可选配IP44防水组件
- 环境温度: -20°~40°
- 重量: 281g

产品规格

- 开孔尺寸: Ø75mm
- 功率: 10W
- 光束角度: 15° 24° 36°
- 天花厚度: 2mm~25mm
- 安装方式: 嵌入式
- 吊顶空间: 大于115mm
- 防眩角度: 40°
- 输入电压: 220~240V~50Hz
- 输入电流: 45mA
- 显指: Ra92
- 色温: 2700K、3000K、3500K、4000K
- 光通量: 525lm、547lm、586lm、674lm (15°)
584lm、609lm、651lm、676lm (24°)
622lm、648lm、693lm、719lm (36°)

以下可调光款为可控硅调光; 0~10V调光:T改为M

2700K		3000K		3500K		4000K	
TFSF2075W10-TB2715		TFSF2075W10-TB3015		TFSF2075W10-TB3515		TFSF2075W10-TB4015	
TFSF2075W10-NB2715		TFSF2075W10-NB3015		TFSF2075W10-NB3515		TFSF2075W10-NB4015	
h(m)	D(cm)	average (lx)	center (lx)	h(m)	D(cm)	average (lx)	center (lx)
1.0	29	3290	4724	1.0	29	3428	4920
2.0	57	823	1181	2.0	57	857	1230
3.0	86	366	525	3.0	86	381	547
4.0	114	206	295	4.0	114	214	308

2700K		3000K		3500K		4000K	
TFSF2075W10-TB2724		TFSF2075W10-TB3024		TFSF2075W10-TB3524		TFSF2075W10-TB4024	
TFSF2075W10-NB2724		TFSF2075W10-NB3024		TFSF2075W10-NB3524		TFSF2075W10-NB4024	
h(m)	D(cm)	average (lx)	center (lx)	h(m)	D(cm)	average (lx)	center (lx)
1.0	39	2093	3055	1.0	39	2180	3183
2.0	79	523	764	2.0	79	545	796
3.0	118	233	340	3.0	118	242	354
4.0	158	131	191	4.0	158	136	199

2700K		3000K		3500K		4000K	
TFSF2075W10-TB2736		TFSF2075W10-TB3036		TFSF2075W10-TB3536		TFSF2075W10-TB4036	
TFSF2075W10-NB2736		TFSF2075W10-NB3036		TFSF2075W10-NB3536		TFSF2075W10-NB4036	
h(m)	D(cm)	average (lx)	center (lx)	h(m)	D(cm)	average (lx)	center (lx)
1.0	62	1028	1571	1.0	62	1071	1636
2.0	123	257	393	2.0	123	268	409
3.0	184	114	175	3.0	184	119	182
4.0	246	64	98	4.0	246	67	102

