



# 防眩天花灯(Ø75)



-  柔光片
-  防眩网
-  防眩杯(亮银)
-  防眩杯(哑黑)
-  防眩杯(白色)

\*可选配件



## 产品特性

灯具颜色: 金属灰+白色面板  
 主体材质: 压铸铝  
 光学系统: 透镜+防眩杯  
 灯具外观: 金属质感  
 投射方向: 垂直0~30°、水平0~355°  
 防护等级: IP20 可选配IP44防水组件  
 环境温度: -20°~40°  
 重量: 263g

## 产品规格

开孔尺寸: Ø 75mm  
 功率: 15W  
 光束角度: 15°、24°、36°、60°  
 天花厚度: 2mm~25mm  
 安装方式: 嵌入式  
 吊顶空间: 大于115mm  
 防眩角度: 40°

输入电压: 220~240V~50Hz  
 输入电流: 70mA  
 显指: Ra92  
 色温: 2700K、3000K、3500K、4000K  
 光通量: 796lm、829lm、887lm、943lm (15°)  
 891lm、928lm、993lm、1030lm (24°)  
 950lm、989lm、1058lm、1098lm (36°)  
 819lm、853lm、912lm、947lm (60°)

以下可调光款为可控硅调光; 0~10V调光:T改为M

色温	可调光	不可调光	光束角	h(m)	D(cm)	average (lx)	center (lx)	光通量
2700K	☑	☐	15°	1.0	29	4986	7157	796
TSF6075W15-TB2715				2.0	57	1246	1789	829
TSF6075W15-NB2715				3.0	86	554	795	887
				4.0	114	312	447	943
3000K	☑	☐	15°	1.0	29	5193	7455	819
TSF6075W15-TB3015				2.0	57	1298	1864	853
TSF6075W15-NB3015				3.0	86	577	828	912
				4.0	114	325	466	947
3500K	☑	☐	15°	1.0	29	5557	7977	819
TSF6075W15-TB3515				2.0	57	1389	1994	853
TSF6075W15-NB3515				3.0	86	617	886	912
				4.0	114	347	499	947
4000K	☑	☐	15°	1.0	29	5909	8483	819
TSF6075W15-TB4015				2.0	57	1477	2121	853
TSF6075W15-NB4015				3.0	86	657	943	912
				4.0	114	369	530	947
2700K	☑	☐	24°	1.0	39	3018	4454	796
TSF6075W15-TB2724				2.0	79	755	1114	829
TSF6075W15-NB2724				3.0	118	335	495	887
				4.0	158	189	278	943
3000K	☑	☐	24°	1.0	39	3144	4640	819
TSF6075W15-TB3024				2.0	79	786	1160	853
TSF6075W15-NB3024				3.0	118	349	516	912
				4.0	158	197	290	947
3500K	☑	☐	24°	1.0	39	3364	4965	819
TSF6075W15-TB3524				2.0	79	841	1241	853
TSF6075W15-NB3524				3.0	118	374	552	912
				4.0	158	210	310	947
4000K	☑	☐	24°	1.0	39	3489	5150	819
TSF6075W15-TB4024				2.0	79	872	1288	853
TSF6075W15-NB4024				3.0	118	388	572	912
				4.0	158	218	322	947
2700K	☑	☐	36°	1.0	62	1573	2386	796
TSF6075W15-TB2736				2.0	123	393	596	829
TSF6075W15-NB2736				3.0	184	175	265	887
				4.0	246	98	149	943
3000K	☑	☐	36°	1.0	62	1639	2485	819
TSF6075W15-TB3036				2.0	123	410	621	853
TSF6075W15-NB3036				3.0	184	182	276	912
				4.0	246	102	155	947
3500K	☑	☐	36°	1.0	62	1754	2659	819
TSF6075W15-TB3536				2.0	123	439	665	853
TSF6075W15-NB3536				3.0	184	195	296	912
				4.0	246	110	166	947
4000K	☑	☐	36°	1.0	62	1819	2758	819
TSF6075W15-TB4036				2.0	123	455	690	853
TSF6075W15-NB4036				3.0	184	202	307	912
				4.0	246	114	172	947
2700K	☑	☐	60°	1.0	91	788	1188	796
TSF6075W15-TB2760				2.0	181	197	297	829
TSF6075W15-NB2760				3.0	271	88	132	887
				4.0	362	49	74	943
3000K	☑	☐	60°	1.0	91	821	1230	819
TSF6075W15-TB3060				2.0	181	205	309	853
TSF6075W15-NB3060				3.0	271	91	138	912
				4.0	362	51	77	947
3500K	☑	☐	60°	1.0	91	879	1324	819
TSF6075W15-TB3560				2.0	181	220	331	853
TSF6075W15-NB3560				3.0	271	98	147	912
				4.0	362	55	83	947
4000K	☑	☐	60°	1.0	91	911	1374	819
TSF6075W15-TB4060				2.0	181	228	343	853
TSF6075W15-NB4060				3.0	271	101	153	912
				4.0	362	57	86	947